



Explore our
PREMIUM PRODUCT COLLECTION

ENVIRONMENTAL & SAFETY SPECIALIST



+255 766 904 668



info@nardalsafety.co.tz



www.nardalsafety.co.tz



P.O. Box 105246, Auditax House, 1st Floor CocaCola Rd,
Plot No. 47 Mikocheni, Dar Es Salaam, Tanzania

CONTENTS

01 ABOUT US

Who we are | Mission | Vision | Values

03 GAS DETECTION

Single Gas | Multi-gas | Fixed Gas | Breathalyzer

04 MONITORING INSTRUMENTS

Noise | Ambient Air | Vibration | Fit Tester

06 RESPIRATORY PROTECTION

Air Purifying (Half Mask/Full Face - Cartridges) | Air Supplied (SCBA, SABA)

06 PROTECTIVE CLOTHING

Gas Tight Suit

07 FALL PROTECTION

Full Body Harness | Lanyard | SRL | Rescue | Anchorage
Davit System | Lifeline | Hoist

08 CONFINED SPACE

Air Blower | Tripod

09 GLOVES

General Purpose | Cut | Chemical | Heat

10 SAFETY FOOTWEAR

11 MISCELLANEOUS

AED | Industrial Lighting | Lockout/Tagout



NARDAL SAFETY offers a one-stop solution for equipment and instruments from trusted, recognized brands. We provide our customers with industry expertise and extensive knowledge of the products we sell.

As part of the PROSAFE Group family, NARDAL SAFETY benefits from nearly 30 years of experience in supplying and distributing Personal Protective Equipment (PPE). Since its founding in 1995, the Group has grown to become one of the largest providers of safety equipment in the region.

Through our international network of suppliers and industry collaborators, we stay up-to-date with the latest approaches to risk assessments, highest international standards, and effective workplace strategies for managing identified risks.

In keeping with our promise to make workplaces safer, we continually enhance our team's professionalism to the highest standard at NARDAL SAFETY.



Our **VISION** is to be the leading provider of premium occupational hygiene, health, safety and environmental equipment, instruments, and consulting services in Tanzania.

Our **MISSION** is going above and beyond by assisting our clients in protecting their people, their neighbour community, and their environment.

Our **VALUES**

- Customer Focused
- Reliability
- Integrity
- Passion

OUR **PARTNERS**



GAS DETECTION

Single Gas | Multi-Gas | Fixed Gas | Breathalyzer

MULTI-GAS DETECTOR MICROCLIP

Honeywell



FEATURES AND BENEFITS

- 4-Gas Detector (H₂S, CO, O₂, LEL).
- Audible, Visual, Vibrating alarm.
- Confidence beep.
- 2 or 3-year warranty (as per model).
- Battery runtime of 18 hours.

MULTI-GAS DETECTOR MULTIRAE LITE

Honeywell



FEATURES AND BENEFITS

- 25 field-interchangeable sensors.
- Local and remote alarms including man-down.
- Available in both diffusion and pump.
- Onboard gas libraries.
- Longest battery run-time in its class.
- Continuous data logging.

SINGLE GAS DETECTOR CLIP

Honeywell



FEATURES AND BENEFITS

- Sensors available (CO, H₂S, SO₂, O₂).
- 2 or 3-year lifetime.
- Maintenance free.
- Affordable, with low cost of ownership.

AREA MONITOR RIGRAT

Honeywell



FEATURES AND BENEFITS

- Up to 6 gas sensors.
- Available in both diffusion and pump.
- Wireless Safety Perimeter.
- Remote monitoring.
- 8 weeks of runtime on a single charge.

VOC MONITOR ULTRARAE 3000+

Honeywell



FEATURES AND BENEFITS

- Accurate VOC, Benzene and Butadiene.
- Battery Run Time: 16 hours.
- Datalogging: Standard 6 months.
- Warranty: 3 years for 10.6 eV lamp.

FIXED GAS DETECTOR SERIES 3000 MKII

Honeywell



FEATURES AND BENEFITS

- Sensors for oxygen and toxic gases.
- Reliable detection.
- Reduced installation & commissioning costs.
- Explosion proof and intrinsically safe.

GAS DETECTION

Single Gas | Multi-gas | Fixed Gas | Breathalyzer

MULTI-GAS DETECTOR VENTIS PRO5

INDUSTRIAL
SCIENTIFIC



FEATURES AND BENEFITS

- Monitor up to 5 gases simultaneously.
- Pumped and diffusion version available.
- Man-down alerts and panic alarms.
- Real-time safety data.

PASSIVE BREATHALYZER ALCOSCAN ACS



FEATURES AND BENEFITS

- One button operation.
- Non-invasive breath testing; perfect for field use.
- Storage and data download.
- Up to 1,000 events (optional).
- Analysis time less than 10 seconds.

BREATHALYZER ALERT J5

ACS



STANDARDS

NHTSA DOT

FEATURES AND BENEFITS

- One button operation.
- Non-invasive breath testing; perfect for field use.
- Storage and data download.
- Up to 1,000 events (optional).
- Analysis time less than 10 seconds.

MONITORING INSTRUMENTS

Noise | Ambient Air | Vibration | Fit Tester

SOUND LEVEL METER OPTIMUS+

Cirrus
Research plc



STANDARDS

IEC 61672-1:2013

FEATURES AND BENEFITS

- Ideal for industrial & environmental noise assessment.
- Periodic LAeq and Ln values, LMax and LMin.
- Measures all parameters simultaneously.
- Class 1 or Class 2 model.
- VoiceTag audio notes and recording.
- Tonal noise detection, 1:1 octaves or 1:3 octaves, etc.

NOISE DOSIMETER DOSEBADGES5

Cirrus
Research plc



STANDARDS

IEC 61672-1:2013

FEATURES AND BENEFITS

- High-performance noise dosimeter.
- RMS Range: 60 dB(A) to 140 dB(A).
- 1:1 Octave Bands (63 Hz to 8kHz).
- 4 simultaneous independent integrator channels.
- Duration, start time & date.
- LAeq/LAVG, Time Weighted Average (LEP,d/LEX,8/TWA).

PERSONAL SAMPLING PUMP VAPEX / APEX2 CASELLA



STANDARDS

ISO13137, IECEx and ATEX certified EX ia IIC T4 Ga

FEATURES AND BENEFITS

- Flow range: 5 - 5000 ml/min.
- Intrinsically Safe.
- Motion Sensor.
- Bluetooth.
- Run time duration and fully programmable timers.
- Logging of flow and motion.

MONITORING INSTRUMENTS

Noise | Ambient Air | Vibration | Fit Tester

MONITORING STATION GUARDIAN2

CASELLAE



STANDARDS

Class 1 to IEC61672-1, IP65

FEATURES AND BENEFITS

- Real-time particulate, noise and ground vibration (PPV).
- Simultaneous PM10, PM2.5 and PM1.0 monitoring.
- Optional VOC sensor measures to 6,000 ppm.
- Optional, maintenance free windspeed & direction sensor.
- Email and text alerts.

HEAT STRESS MONITOR QUESTEMP



STANDARDS

CE Mark, IP54

FEATURES AND BENEFITS

- Utilizes WBGT sensing technology; the standard for heat stress management.
- Dry bulb, wet bulb, and globe temperature.
- WBGT (indoor/outdoor index).
- Heat index (humidex).

PERSONAL DUST SAMPLER SIDEPAK



STANDARDS

EN61326-1:2013, IECEx, ATEX, CSA, IECEx SIM-19.0009X

FEATURES AND BENEFITS

- Real-time mass concentration measurement and data logging for "in-the-field" data analysis.
- Simultaneously measure PM1, PM2.5, PM4, PM10, and 0.8 DPM.
- Audible and visual alarms.
- High-capacity battery.

RESPIRATOR FIT TESTER PORTACOUNT



STANDARDS

IEC61326-1:2013, RoHS Directive 2011/65/EU

FEATURES AND BENEFITS

- Best-in-the-industry respirator Fit Tester.
- Accepted for all full-facepiece and half-facepiece tight fitting elastomeric respirators.
- Built-in N95 Companion™ technology.
- Real-time FitCheck® mode.

INDOOR AIR QUALITY METER IAQ-CALC



FEATURES AND BENEFITS

- Outstanding instruments for investigating and monitoring.
- Measures and data logs multiple parameters such as CO2, temperature, and humidity.
- It calculate dew point, wet bulb temperature and percent of outside air.
- Ergonomic, overmolded case design.

AIR VELOCITY METER VELOCICALC



FEATURES AND BENEFITS

- Simple to operate.
- Measurement range: 0-30 m/s.
- Simultaneously measure temperature and velocity.
- Displays up to 3 measurements simultaneously.
- Calculates volumetric flow and actual/standard velocity.

RESPIRATORY PROTECTION & PROTECTIVE CLOTHING

Air Purifying (Half Mask/Full Face - Cartridges) | Air Supplied (SCBA, SABA) | Gas Tight Suit

HALF MASK 4000 SERIES



STANDARDS

EN 140:1998

FEATURES AND BENEFITS

- Lightest respirator on the market.
- All components in direct contact with user's face are latex free.
- Material: Thermoplastic (R) / Silicone (S).
- Weight: 96 - 114 g.

FULL FACE MASK 5000 SERIES



STANDARDS

EN 136:1998, EN 166, EN 137:2006 Class II

FEATURES AND BENEFITS

- Silicon and thermoplastic models available in 3 different sizes
- Bayonet connection (b-lock).
- Phonic membrane.
- Designed to avoid fogging.
- Scratch resistant visor.

SCBA INTERSPIRO S9



STANDARDS

NFPA 1981:2018 & 1982:2018, NIOSH, 42 CFR part 84 & CBRN

FEATURES AND BENEFITS

- Available as High Pressure 4500 psi or Low Pressure 2216 psi version.
- Unique double pivot feature allows the shoulder straps and waist belt to move independently.
- Airflow: 1350 l/min.
- Heat resistant polymer backplate / Kevlar webbing.

PAPR RPB HX5



STANDARDS

NIOSH, Z89.1, Z87+, IP53

FEATURES AND BENEFITS

- High level of protection and comfort in many applications ranging from grinding to demolition.
- All-in-one hard hat and eye protection unit.
- Filters 99.97% of particles down to 0.12 of a Micron.
- Single fan speed provides 210 slpm.

GAS TIGHT SUIT ALPHATEC SUPER FREEFLOW



STANDARDS

EN 943-1:2015 + A1:2018, EN 1073-1:2016 + A1:2018, EN 14126:2003, EN 1149-5:2008

FEATURES AND BENEFITS

- External air source (SAR): Longer wear, greater comfort.
- Butyl and Viton rubber coating: High chemical resistance.
- Atex compliance: Suitable for work in explosive atmospheres.
- Greater safety in flash fire conditions.
- Enhanced flexibility and durability.

FALL PROTECTION

Full Body Harness | Lanyard | SRL | Rescue | Anchorage | Lifeline | Davit System | Hoist

FULL BODY HARNESS

ADELA



STANDARDS

EN 361

FEATURES AND BENEFITS

- Economical solution for working at height.
- 45 mm width polyester webbing.
- 1 x dorsal D-ring.
- Front chest adjustable belt.
- Detachable waist belt.
- Both thighs pass through buckles.

DOUBLE LANYARD

ADELA



STANDARDS

EN 354 | EN 355

FEATURES AND BENEFITS

- Double 3 strands rope, Dia, 14 mm.
- Length 1.5 m.
- Screw Lock Carabiner AF-09X1.
- Hook H-3101 X 2.

SELF-RETRACTING FALL ARRESTER OLYMPE

KRATOS SAFETY



STANDARDS

EN360:2002, ATEX

FEATURES AND BENEFITS

- Galvanized steel wire rope.
- Length : 6 m.
- Breaking strength : > 12 kN.
- High impact strength polymer casing.
- Max. weight of 140 kg in vertical use.

MOBILE ANCHOR POINT GRAB'N'SLIDE

KRATOS SAFETY



STANDARDS

EN 795:2012 Type B, ATEX

FEATURES AND BENEFITS

- Material: aluminium & brass.
- Breaking strength : greater than 23 kN.
- Designed for beams whose width ranges from 70 mm to 150 mm.

FULL BODY HARNESS AVAO BOD FAST

PETZL



STANDARDS

EN 361, CE EN 358, CE EN 813

FEATURES AND BENEFITS

- Comfortable and versatile harness for work at height.
- Convenient and quick to adjust.
- Easy to carry and organise.
- 5-point attachment.

LOW STRETCH KERNMANTEL ROPE

PETZL



STANDARDS

EN 1891 type A

FEATURES AND BENEFITS

- Good performance in terms of flexibility and weight.
- Low stretch when loaded, increasing efficiency at the start of a rope ascent.
- Consistent performance over time.

FALL PROTECTION

Full Body Harness | Lanyard | SRL | Rescue | Anchorage | Lifeline | Davit System | Hoist

SELF-BRAKING DESCENDER I'D S



STANDARDS

EN 341 type 2 class A, EN 12841 type C, EN 15151-1

FEATURES AND BENEFITS

- Equipped with anti-panic function.
- Rope compatibility: 10 to 11.5 mm.
- Descending a heavy load up to 250 kg.
- Anti-error catch to reduce the risk of an accident.

DOUBLE PULLEY WITH SWIVEL SPIN L2



STANDARDS

EN 12278

FEATURES AND BENEFITS

- Designed for maximum simplicity when setting up haul systems or tyroleans.
- Rope compatibility: 7 to 13 mm.
- Easy handling.
- Efficiency: 95%.

HORIZONTAL LIFELINE



STANDARDS

BS EN-795-C

FEATURES AND BENEFITS

- 5-year warranty.
- Integrated drop and tension indicator.
- Can be used by 3 people.
- Easy passage of intermediate supports with a simple carabiner.

CONFINED SPACE

Air Blower | Tripod

CONFINED SPACE KIT



FEATURES AND BENEFITS

- Body harness with 2 attachment points and an evacuation strap.
- Retractable fall arrestor with integrated rescue winch.
- Work and rescue winch.
- 7 ft. tripod, adaptation kit & transport bag.

MOBILE H-SHAPED BASE DAVIT SYSTEM



FEATURES AND BENEFITS

- For access in confined spaces with a large opening.
- Composed of davit column, davit arm and H-base.
- Equipped with height adjustable feet and spirit levels for correct levelling.
- Opening: 1100 mm - 1510 mm.

AIR MOVER ENDURE



STANDARDS

IP65

FEATURES AND BENEFITS

- Configurable for use with 30 cm & 40 cm ducting.
- High airflow (2095 - 2795 cfm).
- Easy carry handles.
- Use as blower or exhauster.
- Tough and durable.
- Lightweight (19 kg).

GLOVES

General purpose | Cut | Chemical | Heat

GENERAL PURPOSE GLOVES 341



STANDARDS

EN 388:2016+A1:2018 (2121X)

FEATURES AND BENEFITS

- Water-resistant coating on the palm.
- Rough surface grip enables optimum dexterity.
- Elastic wrist cuff.
- Ultimate comfort during long period of time.
- Material: Nylon & polyester.

GENERAL PURPOSE GLOVES AP800



STANDARDS

EN 388:2016+A1:2018 (4111A), EN 16350:2014

FEATURES AND BENEFITS

- Antistatic and safe usage in ATEX zone.
- Embossed microporous foam nitrile palm dip.
- Touchscreen compatible.
- Abrasion-resistant.
- Material: Microfiber.

CUT RESISTANT GLOVES DURACOIL 386



STANDARDS

EN 388:2016+A1:2018 (4X42C)

FEATURES AND BENEFITS

- Provide cut and abrasion resistance, without sacrificing dexterity.
- Microporous nitrile coating disperses oil to increase grip.
- Machine washable & Ergonomic.
- Material: HPPE & polyester.

CHEMICAL RESISTANT GLOVES CS710



STANDARDS

EN 388:2016+A1:2018, EN ISO 374-1:2016+A1:2018/Type A, EN ISO 374-5:2016, EN 407:2020

FEATURES AND BENEFITS

- High protection against a broad range of chemicals.
- Robust durability.
- Good comfort and grip.
- Material: Double-dipped nitrile coating with polyester & seamless knit.
- Length: 300 mm Thickness: 1.47 mm.

CHEMICAL RESISTANT GLOVES 732



STANDARDS

EN 388:2016+A1:2018, EN 18889, EN ISO 374-1:2016+A1:2018/Type A, EN ISO 374-5:2016

FEATURES AND BENEFITS

- Protection against a broad range of chemicals.
- Diamond grip surface finish.
- Flocked liner makes the glove easy to remove.
- Material: Nitrile.
- Length: 330 mm Thickness: 0.15 mm.

HEAT RESISTANT GLOVES 6781R



STANDARDS

EN 388:2016+A1:2018, EN ISO 374-1:2016/TypeA, EN ISO 374-5:2016, EN 407:2020, EN 511:2006

FEATURES AND BENEFITS

- Offer resistance from chemicals, cuts, and abrasion.
- Durable material with rough grip.
- Cold insulation.
- Heat resistant up to 250°C.
- Material: Neoprene with cotton.
- Length: 305 mm.

SAFETY FOOTWEAR

SAFETY SHOES EOLO



STANDARDS

EN ISO 20345:2011 S3 HRO CI WR SRC

FEATURES AND BENEFITS

- High resistance to chemicals.
- Water-stop membrane lining.
- Non-metallic insole.
- High thermal isolation.
- Bi-component sole (rubber-polyurethane).
- Abrasion resistant and antistatic.
- Toe protection.

SAFETY SHOES GOLD



STANDARDS

ISO 20345:2022 S7S FO CI SC SR

FEATURES AND BENEFITS

- High resistance to water infiltration.
- Metal free shoe.
- Polymeric composite toecap.
- Flexible antiperforation composite fabric.
- 3-density antistatic polyurethane sole.
- Anti-shock and anti-slipping.

SAFETY SHOES EDISON



STANDARDS

EN ISO 20345:2012 SB FO E P CI HI WRU HRO SRC

FEATURES AND BENEFITS

- Electrical resistance up to 20.000 V.
- Metal free shoe.
- Polymeric composite toecap.
- Flexible antiperforation composite fabric.
- Bidensity polyurethane and insulating rubber sole resistant to hydrocarbons and to abrasion.

SAFETY SHOES FORWARD 112



STANDARDS

EN ISO 20345:2011 S3 SRC

FEATURES AND BENEFITS

- Upper of strong protection leather.
- Breathable synthetic material.
- Good comfort.
- Removable antistatic insole.
- Nickel-free steel for toecap and midsole.
- Antistatic oil-resistant slip-proof sole.
- Black and orange finish.

SAFETY SHOES TORNADO 133



STANDARDS

EN ISO 20345:2011 S3 SRC

FEATURES AND BENEFITS

- Upper of strong protection leather.
- Breathable synthetic material.
- Good comfort.
- Removable antistatic insole.
- Nickel-free steel for toecap and midsole.
- Antistatic oil-resistant slip-proof sole.
- Reflective inserts on the outer side.

SAFETY SHOES PRIME 545 BLACK



STANDARDS

EN ISO 20345:2011 S3 SRC

FEATURES AND BENEFITS

- Upper of strong protection leather.
- Breathable synthetic material.
- Good comfort.
- Removable antistatic insole.
- Nickel-free steel for toecap and midsole.
- Antistatic oil-resistant slip-proof sole.

MISCELLANEOUS

AED | Industrial Lighting | Lockout/Tagout

AED PLUS

AED PLUS
ZOLL
an Ault-Kasai company



STANDARDS

ISO60601-2-4

FEATURES AND BENEFITS

- Real CPR Help® technology.
- Real-time CPR feedback on compression rate and depth.
- Automatic self-testing.
- Off-the-shelf lithium batteries with a 5-year battery life.
- Rugged design with an IP rating of IP55.

LIGHTING BALLOON

SIROCCO 300 PROPACK



FEATURES AND BENEFITS

- Battery powered LED lighting balloon.
- Suitable for mobile operations.
- Lighted area: 1,017 m².
- Maximum lumen: 22,000 lm.
- Maximum power: 160 W.
- Light efficiency: 345 lux.
- Weight: 2.3 kg.
- Autonomy: up to 12 hrs.

LIGHTING BALLOON

SIROCCO 700



FEATURES AND BENEFITS

- Lighting balloons with the highest light output, the lowest power consumption.
- Lighted area: 3,216 m².
- Maximum lumen: 66,000 lm.
- Maximum power: 500 W.
- Light efficiency: 452 lux.
- Balloon weight: 6,5 kg.

HEADLAMP

PIXA 3R (ATEX)



STANDARDS

ATEX Zone 2/22, II 3 GD Ex nA ic IIB T4 Gc tc IIIC T135°C

FEATURES AND BENEFITS

- Brightness: 90 lm.
- Rechargeable headlamp.
- Suitable for proximity lighting, movement and long-range vision.
- Weight: 145 g.
- Batteries: 3 AAA/LR03 (included).
- CORE rechargeable battery (optional).

HEADLAMP

TIKKINA



STANDARDS

IPX4, ANSI/PLATO FL 1

FEATURES AND BENEFITS

- Brightness: 300 lm.
- Compact & easy-to-use.
- Three lighting levels: MAX BURN TIME, STANDARD and MAX POWER.
- Single button operation.
- Weight: 92 g.
- Batteries: 3 AAA/LR03 (included).
- CORE rechargeable battery (optional).

LOCKOUT/TAGOUT

LOCKOUT/TAGOUT LOCKS & SOLUTIONS



FEATURES AND BENEFITS

As the world's largest padlock manufacturer, Master Lock offers a wide range of security solutions, including padlocks, lockout hasps & cables, electrical lockout devices, mechanical lockout devices, lockout tagout kits, lockout stations, boxes and cabinets, lockout tagout identification labels, etc.



 +255 766 904 668

 info@nardalsafety.co.tz

 www.nardalsafety.co.tz

 P.O. Box 105246, Auditax House, 1st Floor Cocacola Rd,
Plot No. 47 Mikocheni, Dar Es Salaam, Tanzania